

## CERTIFICATE OF COMPLIANCE

## ADB<sup>®</sup> FLIP FLOP HOIST RING ADB<sup>®</sup>'s Quality Management System is registered to ISO 9001:2015

## Date of Issue: 01/02/2024

Compliance Statement: This is to certify that the hoist rings described above have been manufactured and tested in accordance with the specified standards and quality assurance processes and affirms our commitment to delivering quality hoist rings that meet or exceed industry standards. For any inquiries or further information, please contact our customer service team. The following key points confirm compliance:

- 1. Material Quality
  - AISI 4140 or equivalent. Conforms to ASTM A322 and ASTM A108.
- 2. Quality Control
  - Components are heat treated to achieve a hardness range of 36-48 RC and hardness tested for verification.
  - Hoist rings have a design factor of six times the rated capacity in a vertical lift. Hoist rings should not be used to lift loads that exceed the rated capacity.
- 3. Surface Finish
  - Black Oxide
- 4. Environmental Compliances
  - Components are not exposed to equipment or materials known or suspected to contain mercury or polychlorinated biphenyls (PCB's).
- 5. Fastener Specifications
  - Screws are produced from 170,000 PSI minimum tensile strength material.
  - Alloy inch screws conform to ASTM A574.
- 6. Chemical Composition

Carbon	.38/.43	Silicon	.15/.35
Manganese	.75/1.00	Chromium	.80/1.10
Phosphorus	.035/Max	Molybdenum	.15/.25
Sulfur	.040/Max		

Fraudulent Statement: The recording of false, fictitious, or fraudulent statements or entries on this document may be punishable as a felony under federal statue.

Void Statement: Please be advised that this certificate is rendered void if any component(s) are replaced using non-ADB® materials.

Note: This certificate is issued based on the information available at the time of issuance. It serves as a declaration of compliance with the specified standards and quality requirements. Recipients are encouraged to verify the authenticity and validity of this certificate, as well as ensure that the hoist ring(s) are used in accordance with industry and safety standards.

Benjie Bradshaw Vice President/General Manager