



F-Hoist Ring Field Inspection Form

This Form serves as a resource to ADB® Customers for frequent, or periodic field inspection performed on ADB® Products

Inspection Tip: Prior to each lift, it is recommended that each lifting device be inspected visually, and per the conditions set forth below.

Step 1: Fill in the Boxes Below:

Date/Year:		Qualified Person:	
ADB Part Number:		Company:	
Serial Number:		Customer Reference #:	

Step 2: Place an 'X' in the cell that is compliant. If any of the conditions are not met, then remove the lifting device from service immediately until further disposition is reached.

Month	Criteria										
	No Pitting or corrosion	No nicks or Gouges	No excessive thread damage or wear	No bent, twisted, or distorted components	No evidence of unauthorized welding	Ability to rotate freely	No visible damage	No evidence of unauthorized modification	Has manufacturers identification	Has WLL and torque value	
January											
February											
March											
April											
May											
June											
July											
August											
September											
October											
November											
December											

Basic Guidelines for periodic inspection intervals:

1. Normal Service- Yearly
2. Severe Service-Monthly or Quarterly
3. Special Service- As recommended by a qualified person

For more information, contact us @ 1800-423-4425 or visit our website www.adbhoiststrings.com

Information derived from ASME B30.26- Rigging Hardware. This form is not mandatory for ADB® hoist ring use.